

## SUPPLEMENTARY MATERIAL

### GO-TiO<sub>2</sub> as a well-performant photocatalyst maximized by proper parameters selection

Aida M. Díez<sup>1,2,\*</sup>, Yury V. Kolen'ko<sup>1</sup>, Marta Pazos<sup>2</sup> and M. Ángeles Sanromán<sup>2</sup>

<sup>1</sup> Nanochemistry research group, International Iberian Nanotechnology Laboratory, Avenida Mestre José Veiga s/n, 4715-330, Braga, Portugal

<sup>2</sup> CINTECX, Universidade de Vigo, Grupo de Bioingeniería y Procesos Sostenibles, Departamento de Ingeniería Química, Campus Lagoas-Marcosende, 36310 Vigo, Spain.

\*adiez@uvigo.es




Figure S1-SM. Number of publications indexed on Scopus by searching for photocatalysis+ UV, photocatalysis + Visible or photocatalysis+ Visible and UV.

Table S1-SM. Characteristics of the real working matrixes on the study.

Parameter (units)	Physical treated water	Physical+biological treated water
pH	7.5	7.2
Conductivity (mS/cm)	1.135	1.006
Chemical Oxygen Demand (mg O <sub>2</sub> /L)	247	46
Suspended solids (mg/L)	66	19




Figure S2-SM. XRD spectra of  $\text{TiO}_2$  (black) and  $\text{GO-TiO}_2$  (red) catalysts.




Figure S3-SM. FTIR spectra of  $\text{TiO}_2$  (black), GO (green) and  $\text{GO-TiO}_2$  (red) compounds. The insert figure is the zoom in of the spectra between 800 and 3700 nm. Sym. str.=symmetric stretching.

Table S2-SM. Porous characteristics of  $\text{TiO}_2$  and  $\text{GO-TiO}_2$ .

Photocatalyst	Surface area ( $\text{m}^2/\text{g}$ )	Pore volume ( $\text{cm}^3/\text{g}$ )	Pore diameter (nm)
$\text{TiO}_2$	61.265	0.519	34.3
$\text{GO-TiO}_2$	73.197	0.742	39.9




Figure S4-SM. A: UV-Vis spectra of TiO<sub>2</sub> and GO-TiO<sub>2</sub>. B. Tauc plots of both TiO<sub>2</sub> and GO-TiO<sub>2</sub> photocatalysts.




Figure S5-SM. Fitted reactors to the Nyquist results for TiO<sub>2</sub> (a) and GO-TiO<sub>2</sub> (b) catalysts.