

Article

Exploring the Potential to Repurpose Flexible Moulded Polyurethane Foams as Acoustic Insulators

Enikő Mester^{1,2}, Dániel Pecsmány^{1,2}, Károly Jálics³, Ádám Filep^{2,4}, Miklós Varga^{1,2}, Kitti Gráczer^{1,2}, Béla Viskolcz^{1,2}, Béla Fiser^{1,2,5,*}

¹ Institute of Chemistry, University of Miskolc, 3515 Miskolc-Egyetemváros, Hungary

² Higher Education and Industrial Cooperation Centre, University of Miskolc, 3515 Miskolc-Egyetemváros, Hungary

³ Department of Machine Elements, University of Miskolc, 3515 Miskolc-Egyetemváros, Hungary

⁴ Institute of Physical Metallurgy and Metal Forming, University of Miskolc, 3515 Miskolc-Egyetemváros, Hungary,

⁵ Ferenc Rákóczi II. Transcarpathian Hungarian College of Higher Education, 90200 Beregszász, Transcarpathia, Ukraine,

* Correspondence: kemfiser@uni-miskolc.hu

Supplementary information




Figure S1 Average and maximum cell diameters along the sample height of the NCO-0.8 sample examined with a micro-CT before (NCO-0.8, filled circles and squares) and after (NCO-0.8_K, empty circles and squares) dry heat aging.




Figure S2 Average and maximum cell diameters along the sample height of the NCO-0.9 sample examined with a micro-CT before (NCO-0.9, filled circles and squares) and after (NCO-0.9_K, empty circles and squares) dry heat aging.




Figure S3 Average and maximum cell diameters along the sample height of the NCO-1.1 sample examined with a micro-CT before (NCO-1.1, filled circles and squares) and after (NCO-1.1_K, empty circles and squares) dry heat aging.




Figure S4 Average and maximum cell diameters along the sample height of the NCO-1.2 sample examined with a micro-CT before (NCO-1.2, filled circles and squares) and after (NCO-1.2_K, empty circles and squares) dry heat aging.