

Support Information of: Electrospun Poly(L-lactic acid)/Gelatin Hybrid Polymer as A Barrier to Periodontal Tissue Regeneration

Youngchae Cho ¹, Heeseok Jeong ¹, Baeyeon Kim ², Juwoong Jang ³, Yo-Seung Song ^{4,†} and Deuk Yong Lee ^{1,*,+†}

¹ Department of Biomedical Engineering, Daelim University, Anyang 13916, Korea; youngchae6744@naver.com (Y.C.); hsjeong@daelim.ac.kr (H.J.); duke1208@gmail.com (D.Y.L.)

² Department of Materials Science and Engineering, Incheon National University, Incheon 22012, Korea; bykim@incheon.ac.kr

³ Department of R&D Center, Renewmedical Co., Ltd., Bucheon 14532, Korea; orienta@empas.com

⁴ Department of Materials Science and Engineering, Korea Aviation University, Goyang 10540, Korea; yssong@kau.ac.kr

* Correspondence: duke1208@gmail.com (D.Y.L.); yssong@kau.ac.kr (Y.S.)

Supporting Figures:




Figure S1. Mechanical properties of various PLLA membranes.




Figure S2. Mechanical properties of various PLLA/gelatin membranes.




Figure S3. Optical photographs of various PLLA/gelatin membranes soaked in water and water droplets after 5 s of contact with various PLLA/gelatin membranes.






Figure S4. Finger stretched optical photographs of various PLLA/gelatin membranes in dry and wet conditions.




Figure S5. (a) Strength and (b) strain at break of various PLLA/gelatin membranes in dry and wet conditions.





Figure S6. A schematic diagram of biodegradation of PLLA/gelatin membrane.






Figure S7. SEM images ($\times 600$) of surface and cross-section of PLLA/gelatin membranes degraded in medium for 8 weeks at different gelatin concentrations: (a) 0%, (b) 11%, (c) 25%, (d) 30% and (e) 40%. Note that the scale bar is 25 μm .