

Supplementary Material for

**Dye Rejection Efficiencies and Stability Enhancement of
Graphene Oxide-Based Nanofiltration Membranes via Divalent
Cation Intercalation and Mild Reduction**

Hobin Jee ^{1,†}, Jaewon Jang ^{2,†}, Yesol Kang ³, Tasnim Eisa ⁴, Kyu-Jung Chae ⁴, In S. Kim ³
and Euntae Yang ^{1,*}

1 Department of Marine Environmental Engineering, Gyeongsang National University,
Tongyoung 53064, Korea; hbj99@gnu.ac.kr

2 KEPCO Research Institute (KEPRI), Korea Electric Power Corporation (KEPCO), Naju 58277, Korea;
jwjang@gm.gist.ac.kr

3 School of Earth Sciences and Environmental Engineering, Gwangju Institute of Science and Technology
(GIST), Gwangju 61005, Korea; yesol7964@gist.ac.kr (Y.K.); iskim@gist.ac.kr (I.S.K.)

4 Department of Environmental Engineering, Korea Maritime and Ocean University, Busan 49112, Korea;
tasnim.i.eisa@gmail.com (T.E.); kkjdream@kmou.ac.kr (K.-J.C.)

* Correspondence: yet83@gnu.ac.kr

† These authors contributed equally to this work.




Figure S1. EDX mapping of (A) GOM and (B) Mg-GOM.




Figure S2. (A) Photographs of the laminar GO layers after rejection test with a methyl orange dye solution before and after 30-min sonication, and (B) comparison of methyl orange rejection efficiency of the Mg-rGOM(TH) before and after 30-min sonication.