

Effect of Washing on the Electrochemical Performance of a Three-Dimensional Current Collector for Energy Storage Applications

Sajid Ali Ansari ^{1,*}, Nazish Parveen ², Mohd Al Saleh Al-Othoum ¹ and Mohammad Omaish Ansari ³

¹ Department of Physics, College of Science, King Faisal University, P.O. Box 400, Hofuf 31982, Al-Ahsa, Saudi Arabia; malothoum@kfu.edu.sa

² Department of Chemistry, College of Science, King Faisal University, P.O. Box 380, Hofuf 31982, Al-Ahsa, Saudi Arabia; nislam@kfu.edu.sa

³ Center of Nanotechnology, King Abdulaziz University, Jeddah 21589, Saudi Arabia; moansari@kau.edu.sa

* Correspondence: sansari@kfu.edu.sa; Tel.: +966-13-589-9598

The fitted equivalent circuit




Figure S1. The fitted equivalent circuit of the fabricated electrode.

EIS fitted graph of the 3D-NF-C




Figure S2. EIS fitted graph of the 3D-NF-C.

EIS fitted graph of the 3D-NF-etOH




Figure S3. EIS fitted graph of the 3D-NF-etOH.

EIS fitted graph of the 3D-NF-1MH




Figure S4. EIS fitted graph of the 3D-NF-1MH.

EIS fitted graph of the 3D-NF-3MH




Figure S5. EIS fitted graph of the 3D-NF-3MH.