

Supplementary Material

Study of Tribological Properties of Fullerenol and Nanodiamonds as Additives in Water-Based Lubricants for Amorphous Carbon (a-C) Coatings

Shuqing Chen ^{1,*}, Qi Ding ², Yan Gu ¹, Xin Quan ¹, Ying Ma ¹, Yulong Jia ¹, Hongmei Xie ¹ and Jinzhu Tang ^{1,*}

¹ College of Materials Science and Engineering, Yangtze Normal University, Chongqing 408100, China; 20170054@yznu.edu.cn (Y.G.); quanxinjianshe@163.com (X.Q.); yma2017@126.com (Y.M.); yljia2017@126.com (Y.J.); xiehongmei@yznu.cn (H.X.)

² State Key Laboratory of Solid Lubrication, Lanzhou Institute of Chemical Physics, Chinese Academy of Sciences, Lanzhou 730000, China; dingqi@licp.cas.cn

* Correspondence: chenshuqing2021@163.com (S.C.); tangjinzhu11@163.com (J.T.); Tel.: +86-15023512606 (S.C.); +86-18875480116 (J.T.)




Figure S1. (a,b) Digital images of dispersion of fullerenol and nanodiamonds in water with various concentrations (c, wt%). The time for each picture is noted on the respective picture.




Figure S2. (a) Variation of COF with normal load and (b) variation of wear rate with normal load.