



Editorial Nanomechanics and Plasticity

Haifei Zhan ^{1,2}

- ¹ College of Civil Engineering and Architecture, Zhejiang University, Hangzhou 310058, China; zhan_haifei@zju.edu.cn
- ² School of Mechanical, Medical and Process Engineering, Queensland University of Technology (QUT), Brisbane, QLD 4001, Australia

Nanomaterials and nanostructures are continuously driving technology revolutions in broad engineering fields, such as defense [1], aerospace, electronics [2], biomedical [3,4], energy [5], and other high-end sectors. Landmark nanostructures, such as fullerene [6], carbon nanotube (CNT) [7], and graphene [8], have significantly promoted the growth of nanomaterials and triggered novel applications. For instance, there are increasing interests in the synthetic nanochannels (e.g., graphene nanochannels), which possess unique transmission behavior and show appealing prospects for nanofiltration [9,10], water desalination [11–14], and energy storage [15,16]. Through atomistic simulations, Li et al. [17] investigated the permeability of a hexagonal diamond nanochannel for a NaCl solution. To facilitate various engineering implementations, a comprehensive understanding of their mechanical properties and deformation mechanisms is usually a prerequisite, which can be acquired through nanoscale experiments and atomistic calculations.

Extensive works have been conducted to extend the concepts/theories established at macro-scale to nanoscale, in order to describe the mechanical behavior of nanomaterials. For instance, surface effects and axial extension have been incorporated in the beam theory to describe the bending and vibration of nanowires [18,19], which are the building blocks for nanoelectromechanical systems. Considering the coupled loading scenarios, Lu et al. [20] investigated the deformation mechanisms of nanowire under coupled tension-torsion loads. Pan et al. [21] derived the exact solutions for torsion and warping of axial-loaded beam-columns in order to avoid the underestimation of the torsional stiffness of thinwalled nanostructures. With the advancement of fabrication technology, more complex nanostructures have been reported, such as heterostructures, Janus structures, helical/spiral structures [22], nanoscrolls [23], and three-dimensional networks [24]. These complex structures exhibit unique physical and chemical properties. For instance, Yang et al. [25] found that the Janus WSSe and MoSSe monolayers exhibit a strong mechanical anisotropy under tension.

A common utilization of nanomaterials is reinforcement for engineering materials, which includes polymers, fibers and metals [26]. Extensive works have employed lowdimensional nanomaterials to enhance the mechanical and thermal properties of composite materials [27,28]. For instance, the CNT has excellent mechanical properties, which is promising for artificial muscles and flexible electronics, while the mechanical performance of CNT fibers/bundles depend on various factors, such as the alignments and compositions of constituent CNTs as shown by Wei et al. [29]. The excellent mechanical properties of nanomaterials also make them promising for extreme applications, such as the protective shields that alleviate the damage from the hyper-velocity impact. In this regard, Xia et al. [30] investigated the deformation and penetration mechanisms of titanium carbide MXene nanosheets. Studies reveal that many factors affect the mechanical performances of polymer composites synergistically, such as the type, percentage, alignment, dispersion, and functional groups of the nanofillers [31]. Investigations show that CNT acts as a skeleton in the poly phenylene terephthalamide polymer that enhance both the strength and



Citation: Zhan, H. Nanomechanics and Plasticity. *Nanomaterials* 2022, 12, 3807. https://doi.org/10.3390/ nano12213807

Received: 20 October 2022 Accepted: 26 October 2022 Published: 28 October 2022

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2022 by the author. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https:// creativecommons.org/licenses/by/ 4.0/). modulus [32], and the graphene foam can remarkably increase the storage modulus and loss modulus of the polydimethylsiloxane polymer [33].

Besides nanomaterials, plenty of works have investigated the atomistic underlying mechanisms for the mechanical behaviors of engineering materials, which provides useful guidelines for the design of high-performance materials. For example, Wu et al. [34] probed the penetration process of aluminum nanorod through atomistic simulations, and Wan et al. [35] assessed how the initial void influence the damage characteristic of single crystal aluminum under shock loading. Interestingly, Jiang et al. [36] found that the presence of copper nanoparticle will trigger the formation of regular stacking fault in the single crystal aluminum under shock compression. Based on the smoothed particle hydrodynamics (SPH) method, Wu et al. [37] discussed the differences in the fragmentation characteristics between the microscopic (atomic scale) and macroscopic scales under hypervelocity impact. In real applications, materials are usually exposed under a complex loading environment, e.g., electronics experience cyclic thermal and mechanical loadings during service [38]. As such, it is crucial to explore the responses of materials under coupled loading. For example, Zhao et al. [39] established a multiscale model to investigate the mechanical-thermal responses of woven composites. There is also increasing attention being devoted to the strain engineering of nanomaterials. For instance, Yang et al. [40] reported that proper strain can modulate the valley polarization in VS2 heterostructures. Other works also reported the strain tailored thermal transport properties [41] and interfacial thermal conduction of nanostructures [42].

In summary, this Special Issue of Nanomaterials entitled "Nanomechanics and Plasticity" compiles a series of original research articles that explore the mechanics at nanoscale for different advanced materials. We are confident that this Special Issue will provide the reader with an overall view of some of the latest prospects in the nanotechnology field.

Funding: H.Z. would like to thank the financial support from Zhejiang Provincial Natural Science Foundation (LR22A020006) and the National Natural Science Foundation of China (12172325).

Data Availability Statement: Not applicable.

Acknowledgments: A special thank you to all the colleagues who submitted their research work to the Special Issue "Nanomechanics and Plasticity".

Conflicts of Interest: The authors declare no conflict of interest.

References

- Sankaran, S.; Deshmukh, K.; Ahamed, M.B.; Khadheer Pasha, S.K. Recent advances in electromagnetic interference shielding 1. properties of metal and carbon filler reinforced flexible polymer composites: A review. Compos. Part A 2018, 114, 49–71. [CrossRef] 2.
- Zhang, A.; Lee, J.-H.; Lieber, C.M. Nanowire-enabled bioelectronics. Nano Today 2021, 38, 101135. [CrossRef]
- 3. Liu, F.; Kang, H.; Liu, Z.; Jin, S.; Yan, G.; Sun, Y.; Li, F.; Zhan, H.; Gu, Y. 3D Printed Multi-Functional Scaffolds Based on Poly(epsilon-Caprolactone) and Hydroxyapatite Composites. Nanomaterials 2021, 11, 2456. [CrossRef]
- 4. Wong, F.; Dey, K.K.; Sen, A. Synthetic Micro/Nanomotors and Pumps: Fabrication and Applications. Annu. Rev. Mater. Res. 2016, 46, 407–432. [CrossRef]
- 5. Wang, K.; Yuan, M.; Cao, X.; Ding, C.; Ma, J.; Wei, Z. Effect of Hydrothermal Method Temperature on the Spherical Flowerlike Nanostructures NiCo(OH)4-NiO. Nanomaterials 2022, 12, 2276. [CrossRef] [PubMed]
- 6 Kroto, H.W.; Heath, J.R.; Obrien, S.C.; Curl, R.F.; Smalley, R.E. C-60-Buckminsterfullerene. Nature 1985, 318, 162-163. [CrossRef]
- 7. Iijima, S. Helical microtubules of graphitic carbon. Nature 1991, 354, 56–58. [CrossRef]
- 8. Geim, A.K.; Novoselov, K.S. The rise of graphene. Nat. Mater. 2007, 6, 183–191. [CrossRef]
- 9. Park, H.B.; Kamcev, J.; Robeson, L.M.; Elimelech, M.; Freeman, B.D. Maximizing the right stuff: The trade-off between membrane permeability and selectivity. Science 2017, 356, 10. [CrossRef]
- Zhu, H.J.; Wang, Y.Y.; Fan, Y.Q.; Xu, J.B.; Yang, C. Structure and transport properties of water and hydrated ions in nano-confined 10. channels. Adv. Theory Simul. 2019, 2, 18. [CrossRef]
- Werber, J.R.; Osuji, C.O.; Elimelech, M. Materials for next-generation desalination and water purification membranes. Nat. Rev. 11. Mater. 2016, 1, 16. [CrossRef]
- Li, C.Y.; Meckler, S.M.; Smith, Z.P.; Bachman, J.E.; Maserati, L.; Long, J.R.; Helms, B.A. Engineered transport in microporous 12. materials and membranes for clean energy technologies. Adv. Mater. 2018, 30, 33. [CrossRef] [PubMed]

- 13. Ige, E.O.; Arun, R.K.; Singh, P.; Gope, M.; Saha, R.; Chanda, N.; Chakraborty, S. Water desalination using graphene oxideembedded paper microfluidics. *Microfluid. Nanofluid.* 2019, 23, 8. [CrossRef]
- 14. Han, X.; Wang, W.P.; Zuo, K.C.; Chen, L.; Yuan, L.; Liang, J.; Li, Q.L.; Ajayan, P.M.; Zhao, Y.; Lou, J. Bio-derived ultrathin membrane for solar driven water purification. *Nano Energy* **2019**, *60*, 567–575. [CrossRef]
- 15. Elimelech, M.; Phillip, W.A. The future of seawater desalination: Energy, technology, and the environment. *Science* **2011**, *333*, 712–717. [CrossRef]
- 16. Yusuf, H.; Annuar, M.S.M.; Subramaniam, R.; Gumel, A.M. Amphiphilic biopolyester-carbon nanotube anode enhances electrochemical activities of microbial fuel cell. *Chem. Eng. Technol.* **2019**, *42*, 566–574. [CrossRef]
- 17. Li, B.; Dong, B.; Shi, T.; Zhan, H.; Zhang, Y. Atomistic Simulations of the Permeability and Dynamic Transportation Characteristics of Diamond Nanochannels. *Nanomaterials* **2022**, *12*, 1785. [CrossRef]
- 18. Yun, G.; Park, H. Surface stress effects on the bending properties of fcc metal nanowires. Phys. Rev. B 2009, 79, 195421. [CrossRef]
- 19. Zheng, X.P.; Cao, Y.P.; Li, B.; Feng, X.Q.; Wang, G.F. Surface effects in various bending-based test methods for measuring the elastic property of nanowires. *Nanotechnology* **2010**, *21*, 205702. [CrossRef]
- Lu, H.; Dong, B.; Zhang, J.; Lü, C.; Zhan, H. Deformation of Copper Nanowire under Coupled Tension and Torsion Loading. Nanomaterials 2022, 12, 2203. [CrossRef]
- Pan, W.-H.; Zhao, C.-H.; Tian, Y.; Lin, K.-Q. Exact Solutions for Torsion and Warping of Axial-Loaded Beam-Columns Based on Matrix Stiffness Method. *Nanomaterials* 2022, 12, 538. [CrossRef] [PubMed]
- Wu, J.; Hu, Z.; Jin, Z.; Lei, S.; Guo, H.; Chatterjee, K.; Zhang, J.; Yang, Y.; Li, B.; Liu, Y.; et al. Spiral Growth of SnSe2 Crystals by Chemical Vapor Deposition. *Adv. Mater. Interfaces* 2016, *3*, 1600383. [CrossRef]
- Zhan, H.; Dong, B.; Zhang, G.; Lü, C.; Gu, Y. Nanoscale Diamane Spiral Spring for High Mechanical Energy Storage. Small 2022, 18, 2203887. [CrossRef]
- Kong, Q.; Bodelot, L.; Lebental, B.; Lim, Y.D.; Shiau, L.L.; Gusarov, B.; Tan, C.W.; Liang, K.; Lu, C.; Tan, C.S.; et al. Novel three-dimensional carbon nanotube networks as high performance thermal interface materials. *Carbon* 2018, 132, 359–369. [CrossRef]
- Yang, F.; Shang, J.; Kou, L.; Li, C.; Deng, Z. Mechanical Behaviors in Janus Transition-Metal Dichalcogenides: A Molecular Dynamics Simulation. *Nanomaterials* 2022, 12, 1910. [CrossRef] [PubMed]
- 26. Li, Y.; Pei, X.; Zhang, H.; Yuan, M. A First-Principle Study of Interactions between Magnesium and Metal-Atom-Doped Graphene. *Nanomaterials* **2022**, *12*, 834. [CrossRef] [PubMed]
- 27. Zhan, H.; Nie, Y.; Chen, Y.; Bell, J.M.; Gu, Y. Thermal Transport in 3D Nanostructures. *Adv. Funct. Mater.* **2019**, *30*, 1903841. [CrossRef]
- 28. Sun, R.; Melton, M.; Safaie, N.; Ferrier, R.C.; Cheng, S.; Liu, Y.; Zuo, X.; Wang, Y. Molecular View on Mechanical Reinforcement in Polymer Nanocomposites. *Phys. Rev. Lett.* **2021**, *126*, 117801. [CrossRef]
- Wei, H.; Ting, H.Z.J.; Gong, Y.; Lu, C.; Glukhova, O.E.; Zhan, H. Torsional Properties of Bundles with Randomly Packed Carbon Nanotubes. *Nanomaterials* 2022, 12, 760. [CrossRef]
- Xia, K.; Zhan, H.; Zhang, X.; Li, Z. Atomistic Investigation of the Titanium Carbide MXenes under Impact Loading. *Nanomaterials* 2022, 12, 2456. [CrossRef]
- 31. Li, C.; Nie, Y.; Zhan, H.; Bai, J.; Liu, T.; Gu, Y. Mechanical properties of polymer nanocomposites with randomly dispersed and cross-linked two-dimensional diamond. *Compos. Sci. Technol.* **2022**, 230, 109722. [CrossRef]
- Li, T.; Mao, Z.; Du, J.; Song, Z. Structure and Nanomechanics of PPTA-CNT Composite Fiber: A Molecular Dynamics Study. Nanomaterials 2022, 12, 3136. [CrossRef]
- Li, T.; Du, J.; Xu, M.; Song, Z.; Ren, M. Lightweight and Flexible Graphene Foam Composite with Improved Damping Properties. Nanomaterials 2022, 12, 1260. [CrossRef] [PubMed]
- 34. Wu, Y.-C.; Liu, J.-M.; Xie, W.; Yin, Q.; Shao, J.-L. Atomistic Simulations on Metal Rod Penetrating Thin Target at Nanoscale Caused by High-Speed Collision. *Nanomaterials* **2021**, *11*, 3160. [CrossRef]
- Wan, Y.-T.; Shao, J.-L.; Yu, G.-Z.; Guo, E.-F.; Shu, H.; Huang, X.-G. Evolution of Preset Void and Damage Characteristics in Aluminum during Shock Compression and Release. *Nanomaterials* 2022, *12*, 1853. [CrossRef] [PubMed]
- Jiang, D.-D.; Chen, P.-Y.; Wang, P.; He, A.-M. Spallation Characteristics of Single Crystal Aluminum with Copper Nanoparticles Based on Atomistic Simulations. *Nanomaterials* 2021, 11, 2603. [CrossRef] [PubMed]
- Wu, W.-D.; Liu, J.-M.; Xie, W.; Xing, Y.; Shao, J.-L. Microscopic and Macroscopic Fragmentation Characteristics under Hypervelocity Impact Based on MD and SPH Method. *Nanomaterials* 2021, 11, 2953. [CrossRef] [PubMed]
- Depiver, J.A.; Mallik, S.; Amalu, E.H. Thermal fatigue life of ball grid array (BGA) solder joints made from different alloy compositions. *Eng. Fail. Anal.* 2021, 125, 105447. [CrossRef]
- Zhao, X.; Guo, F.; Li, B.; Wang, G.; Ye, J. Multiscale Simulation on the Thermal Response of Woven Composites with Hollow Reinforcements. *Nanomaterials* 2022, 12, 1276. [CrossRef]
- Yang, F.; Shang, J.; Kou, L.; Li, C.; Deng, Z. Controllable Valley Polarization and Strain Modulation in 2D 2H/VS2/CuInP2Se6 Heterostructures. *Nanomaterials* 2022, 12, 2461. [CrossRef]
- Cheng, Y.; Wu, X.; Zhang, Z.; Sun, Y.; Zhao, Y.; Zhang, Y.; Zhang, G. Thermo-mechanical correlation in two-dimensional materials. Nanoscale 2021, 13, 1425–1442. [CrossRef] [PubMed]
- 42. Ren, K.; Qin, H.; Liu, H.; Chen, Y.; Liu, X.; Zhang, G. Manipulating Interfacial Thermal Conduction of 2D Janus Heterostructure via a Thermo-Mechanical Coupling. *Adv. Funct. Mater.* **2022**, *32*, 2110846. [CrossRef]