



Inkjet-Printed Silver Nanowire Ink for Flexible Transparent Conductive Film Applications

Shuyue Wang ^{1,†}, Xiaoli Wu ^{1,2,†}, Jiaxin Lu ¹, Zhengwu Luo ¹, Hui Xie ¹, Xiaobin Zhang ¹, Kaiwen Lin, ^{1,*} and Yuehui Wang ^{1,*}

¹ Zhongshan Institute, University of Electronic Science and Technology of China, Guangdong, Zhongshan 528402, China; shuyewang125@163.com (S.W.); 201921030315@std.uestc.edu.cn (X.W.); JIAC13509809967@163.com (J.L.); luozhengwu128@163.com (Z.L.); Xiehuizsedu@126.com (H.X.); zhangxiaobin@redsolar.com.cn (X.Z.)

² Department of Material and Energy, University of Electronic Science and Technology of China, Chengdu 610054, China

* Correspondence: wyh@zsc.edu.cn (Y.W.); 201610102331@mail.scut.edu.cn (K.L.); Tel.: +86-760-8832-5402

† These authors contributed equally to this work.

Citation: Wang, S.; Wu, X.; Lu, J.; Luo, Z.; Xie, H.; Zhang, X.; Lin, K.; Wang, Y. Fabrication of Inkjet Printability Silver Nanowires Ink with High Concentration and Its Application in Flexible Transparent Pattern Circuit. *Nanomaterials* **2022**, *12*, 842. <https://doi.org/10.3390/nano12050842>

Academic Editor(s): Christian Falconi and Andrew Pike

Received: 13 December 2021

Accepted: 23 February 2022

Published: 2 March 2022

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2022 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).




Figure S1. Jetting waveform parameters and voltage.




Figure S2. Photographs of the as-prepared AgNWs inks in Table 1 placed in the refrigerator (8°C) for 0, 3, 15 and 40 days, respectively.




Figure S3. Photographs of Contact Angle of AgNWs inks shown in Table 1.




Figure S4. Relationship between sheet resistance and transmittance of inkjet printed silver nanowires flexible transparent conductive film in different literatures.




Figure S5. FOM of AgNWs films with different printing layers.